

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(3)



Consommation
et Corporations Canada
Bureau des brevets
Ottawa, Canada
K1A 0G9

Consumer and
Corporate Affairs Canada (21) (A1)
Patent Office (22)
(43)
(52)

2,025,902
1990/09/21
1992/03/22
301-37

(51) INTL. CL. ⁵ B60B-7/02; B60B-7/00

(19) (CA) APPLICATION FOR CANADIAN PATENT (12)

(54) ~~_____~~

(72) Douglas, Darren - Canada ;

(73) Same as inventor

(57) 2 Claims

50997-82

Notice: The specification contained herein as filed

Canada

CCA 3254 (10-89) 41

2025902

Form 24
(ss.21,31,34,and 142)

ABSTRACT

A flat piece of plastic (or material) to go between the hub and rim of a vehicle. It can be any color;(ie: pink, green,yellow, ...) The holes can be punched out to addapt to any make of vehicle. (Ford, Chev., Dodge....) This is a ~~simple device~~ ~~to be used~~ while ~~driving~~ ~~on a road~~ and also protects rim from chipping caused by flying rock from inside-under tire. Must remove tire to set in place. Model has makeshift holes in place to punch out for studs.

Derivative

CLAIM

2025902

The embodiments of the invention in which an exclusive property or privilege is claimed as defined as follows;

1. A piece of plastic cut to fit between the rim and hub of a vehicle ~~for protection~~
~~thereof~~
2. A tool as defined in claim 1, in which the invention is used to protect hub or rims of a vehicle.

SPECIFICATION

This invention relates to improving the looks
of the form and offering protection at the same
time.

Most slotted rims are open except for the chrome which leaves room for rooks to fly back and forth.

This invention prevents this from happening thereby offering some protection. With the option of being ~~flamable~~ and adding ~~to the mass~~ to otherwise dull films.

The diameter of the invention depends entirely on the rim size. To install this invention, it would require the removal of the tire and rim, and placed between the hub and the rim.

The width is approximately 1/16 inch so as not to hinder the operation of the vehicle.

To construct this invention, you would have to find the diameter, i.e. 16 inch round and proceed to [REDACTED] to that calculation. Then cut out a round hole to accommodate the hub of the wheel. Lastly, you punch out holes to accommodate the studs.